



REGOMS PRODUCT DATASHEET

4X5 CENTRIFUGAL PUMP

4x5 CENTRIFUGAL PUMP



FOR ILLUSTRATION PURPOSE ONLY

SPECIFICATION	DESCRIPTION
PUMP	- Pump Model: SERVA SCP 5x4 - Flowrate: 12 bbl/min - Shaft Seal: Single, high quality mechanical seal fitted as standard to all pumps. Different seals are possible on application. Standard seal operating temperature 95°C.
ENGINE	- Engine Model: Detroit Diesel 3-71 Engine - Arrangement: 3 Cyl in-line - Displacement: 213 cubic inches, 4 main bearings. - Lube Oil Pressure: 30 – 60 psi @ 1,200 rpm, 38 – 60 psi @ 1,800 rpm and 40 – 60 psi @ 2,000 rpm - Horse Power (BHP): 66 hp @ 1,200 rpm, 84 hp @ 1,600 rpm, 97 hp @ 2,000 rpm
WEIGHT	MGW 2.5 MT
DIMENSION	(2.80L x 1.30W x 1.70H) m

For a quotation and detailed pricing, please contact our sales team:

REGOMS Engineering (M) Sdn. Bhd. No.
10-1, Jalan 13/48A, The Boulevard Shop
Office Sentul Raya, Sentul Selatan, 51000
KL. WP.
Malaysia
Tel : +603 2858 2600
Email : sales1@regoms.com

REGOMS Australia Pty Ltd. Level 1, 16,
McDougall Street,
PO Box 1279, MILTON QLD 4064
Australia
M: +614 0008 4977
F: +617 3198 2401
E : sri@regoms.com
<https://www.regoms.com>