



REGOMS PRODUCT DATASHEET

NON-ZONE RATED EXTERNAL DIESEL TANK

NON ZONE RATED EXTERNAL DIESEL TANK



FOR ILLUSTRATION PURPOSES ONLY

The **NON-ZONE RATED EXTERNAL DIESEL TANK** is a robust, transportable, and fully certified self-bunded diesel storage tank engineered to meet the highest standards of safety, compliance, and mobility. Designed for demanding industrial and remote applications, this tank offers a safe fill capacity of 1000L- 110,000L and is fully baffled for transport, allowing for secure movement even when filled.

Built to AS1940, AS1692, UN31AY, UL142, ULC-S601, and ULC-S653 standards, it is ideal for fuel storage and dispensing in sectors such as mining, construction, agriculture, renewable energy, and remote operation.

NON-ZONE RATED EXTERNAL DIESEL TANK	
MODEL RANGE	1000L – 110,000L
TANK TYPE	SELF BUNDED(DOUBLE-WALLED) STEEL TANK
CONSTRUCTION	HEAVY DUTY MILD STEEL WITH CORROSION RESISTANT COATING
BUNDING	110%
TANK ACCESS	LOCKABLE MANWAY WITH FILL POINT, DIPSTICK, AND INSPECTION HATCH
DISPENSING SYSTEM	OPTIONAL 12V/24V/240V ELECTRIC PUMP, FLOW METER, HOSE REEL
DESIGN STANDARD	AS1692 / AS1940 / UL142/ ISO STANDARDS (MODEL DEPENDENT)
OVERFILL PROTECTION	MECHANICAL OR ELECTRONIC OVERFILL PREVENTION DEVICE
VENTING	PRESSURE AND VACUUM RELIEF VENT WITH FLAME ARRESTOR
LIFTING AND TRANSPORT	INTEGRATED LIFTING LUGS AND 4-WAY FORKLIFT POCKETS
CERTIFICATIONS	COMPLIES WITH EPA, WORKSAFE, AND OTHER AUSTRALIAN REGULATIONS
ELECTRICAL PROTECTION	EARTHING STAKE AT EXTERNAL TANKS JOINTS
FUEL GAUGE	MECHANICAL LEVEL GAUGE